SALES BROCHURE

S 55

SCREW COMPRESSOR 5.5 KW

The screw compressor for workshops that run all day long.

Supplied without air receiver or dryer, to be connected to your compressed air network.



5.5 kW	8 · 10 · 13 bar	0.6 m³/min	65 to 68 ± 2 dB	380 V
MOTOR POWER	PRESSURE	AIR FLOW	NOISE LEVEL	POWER SUPPLY THREE-PHASE / 50 HZ

KEY FEATURES

At the heart of the machine is a **high-efficiency screw air-end** in **direct drive** from a **rare-earth permanent magnet motor** (insulation class F). It starts through a **variable frequency drive**: no current surge on your electrical installation. An **electronic controller with display** constantly monitors pressure, temperature and running hours, and protects the machine if anything goes wrong. You set the working pressure: thanks to **variable speed**, the motor adjusts its speed to your air consumption to hold that pressure, and stops on its own when nothing is drawing air.

- Air-cooled; compressed air at most 15 °C above ambient temperature, oil content 3 to 5 ppm.
- Standard wear parts (filters, oil, separator): maintenance stays simple and affordable.
- Compact footprint (750 × 550 × 750 mm, 98 kg): it fits in a small workshop.
- Every machine is checked and tested before shipping.

WHY CHOOSE A SCREW COMPRESSOR?

A piston compressor is made for occasional use. As soon as compressed air is needed several hours a day, a screw compressor takes over: it runs all day long, more quietly.

	S 55, SCREW COMPRESSOR	PISTON COMPRESSOR
Duty	**Continuous operation, all day long**	Intermittent use, needs rest periods
Noise	**Quiet: it can stay in the workshop**	Much louder, often moved outside
Air	**Steady flow, no surges or pulsations**	Saw-tooth pressure between starts
Wear	**High-efficiency screw block, standard wear parts**	Valves, rings and belts stressed at every cycle
Energy use	**Variable speed: the motor follows demand and stops when nothing is using air**	On/off operation at full power

WHICH TRADES IS IT FOR?

Car garage · Body shop · Tyre centre · Joinery · Metal fabrication · Agriculture · Upholstery and trim shop · Car detailing · Printing and packaging · Quiet workshop (near offices)

2 YEARS

2-YEAR WARRANTY

- Every machine is checked and tested before shipping
- Documentation and maintenance logbook supplied
- Spare parts available for 15 years

COMPLETE THE INSTALLATION

Tank, refrigerated dryer, filters, hoses and fittings: we advise you on the right setup for your tools and your work pace.

SPECIFICATIONS

Power	**5.5 kW**
Technology	**Screw compressor, permanent magnet motor, direct drive, variable speed**
Maximum pressure	**8, 10 or 13 bar, to choose**
Air flow (ISO 1217)	**0.6 m³/min at 8 bar; 0.52 m³/min at 10 bar; 0.42 m³/min at 13 bar**
Air receiver	**No air receiver**
Power supply	**380 V three-phase / 50 Hz**
Cooling	**Air-cooled**
Noise level	**65 to 68 ± 2 dB(A)**
Outlet connection	**G 1/2"**
Dimensions	**750 × 550 × 750 mm (L × W × H)**
Weight	**98 kg**
Service intervals	**500 hours, then every 1,500 hours (reminder shown by the controller)**

CONTACT US
www.airstahl.com
+33 4 82 53 40 02
contact@airstahl.com